



مارمكس اف دبليو بي ٢٠٠
MARMIX FWP200

MARMIX FWP200



مارمكس اف دبليو بي ٢٠٠ عبارة عن خليط مسحوق متكامل مانع لتسرب الماء عالي الجودة وسهل الاستخدام مصمم للاستخدام في جميع أنواع الخلطات القائمة على الأسمنت. تم تركيب ماركس اف دبليو بي 200 بمزيج فريد من العناصر العضوية وغير العضوية المختارة بعناية، ويتم تصنيعه تحت ظروف مراقبة لضمان منتج ثابت وعالي الجودة. يقوم ماركس اف دبليو بي ٢٠٠ بإغلاق سطح المواد الأسمنتية فعليًا، مما يخلق نظامًا ذو نفاذية منخفضة.

↳ MARMIX FWP200 is a high-grade, easy-to-handle powder integral waterproofing admixture designed for use in all types of cement-based mixes. MARMIX FWP200 is formulated with a unique hydrophobic blend of carefully selected organic and inorganic ingredients, manufactured under controlled conditions to ensure a consistent and high-quality product. MARMIX FWP200 physically seals the surface of the cementitious material, creating a system with low permeability.

نظرة عامة على المنتج PRODUCT OVERVIEW

- » It reduces water permeability and absorption,
- » As well as chloride intrusion.
- » The hydrophobic ingredients are insoluble in water, becoming a permanent constituent of the hardened cementitious material.
- » MARMIX FWP200 improves chemical and carbonation resistance,
- » Enhances workability and mechanical strength,
- » Does not alter the setting time of cement.

20
KG



WWW.MARKHORSA.COM

MARMIX FWP200

POWDERED WATERPROOFING ADMIXTURE FOR MORTAR

DESCRIPTION

Marmix FWP200 is a powdered waterproofing admixture, which blocks the capillaries and pores in Portland cement/sand mortars preventing the movement of moisture.

USES

Marmix FWP200 is used to waterproof Portland cement/sand renders and mortars for application to:

- Walls
- Facades
- Floor toppings
- Jointing mortars

CHARACTERISTICS / ADVANTAGES

- Easy to use
- Economical
- Convenient powdered form
- Watertight, but vapour permeable
- Chloride free



PRODUCT INFORMATION

Packaging	1x20 kg.
Shelf life	12 Months in original, unopened container.
Storage conditions	Store in a dry area between 5°C and 40°C. Protect from direct sunlight

Fasteners should be driven with a variable speed electric screwdriver (at no more than 1500rpm) and TX25 drive bar, within three degrees perpendicular to the surface of the fastened material. Avoid overdriving, and do not over-tighten.

First aid measures

General advice : Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air. Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person

Note : Operating Temperature should not exceed 50 Degrees Celcius

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product (s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchasers' responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.