

## غراء للبلاط والسيراميك TILE ADHESIVE



غراء البلاط الخاص بشركة مارخور هو خيارك الأفضل فإنه لا يقدم التصاق مثالي فقط ولكنه أيضا خالي من المذيبات. سواء كان للاستخدام الداخلي أو الخارجي، أو للمباني الجديدة أو لتجديد المباني القديمة أو تبييط حمام صغير أو حوض سباحة كبير ، أو للاستخدامات الخاصة أو الصناعية ، كن واثقا من أن مصنع مارخور لديه الحلول المناسبة بمجموعاته الواسعة من المنتجات المتوافقة تماما. بفضل خبرتها وتطوير التقنيات الجديدة ، توفر منتجاتنا للتبييط أفضل أداء ومثانة حيث يتم تنفيذ عملية التبييط بشكل أسرع وبأقل جهد.

MAR TILE FIX is a cementitious mortar adhesive composed of hydraulic binders, selected aggregates, and special additives. It is supplied as a dry powder in pre-weighed bags ready to use on-site, which requires only the addition of clean water to produce easily workable mortar. MAR TILE FIX is ideal for fixing Ceramic Tiles, Terrazzo Tiles. MAR TILE FIX is applied in thickness from 3mm to 10mm depending upon the substrate's type of tiles and quality





## ADVANTAGES

- » Factory controlled pre-blend ensures consistently high quality.
- » Requires only the addition of water on-site at the time of usage.
- » Easy tile installation that enables high productivity.
- » Superior workability.
- » Excellent Adhesion to a variety of ceramic tiles available in the local market.
- » Water-resistant
- » Suitable for internal applications
- » Suitable for horizontal & vertical surfaces



### Product Information:

<b>Markhor Tile Adhesive</b> Product Name: Tile Adhesive Physical form: Powder Colour: White Mixture	<b>تقنية المانية</b> GERMAN FORMULATED 												
<b>COMPOSITION/ INGREDIENT COMPONENTS</b>													
<table border="1"> <thead> <tr> <th>Chemical NAME</th> <th>Percentage</th> </tr> </thead> <tbody> <tr> <td>HPMC</td> <td>0.26-0.28</td> </tr> <tr> <td>RDP</td> <td>0.17-0.19</td> </tr> <tr> <td>WHITE CEMENT</td> <td>4.70-4.76</td> </tr> <tr> <td>SALICA SAND</td> <td>7.10-7.14</td> </tr> <tr> <td>CALCIUM CARBONATE</td> <td>8.1.8.3</td> </tr> </tbody> </table>	Chemical NAME		Percentage	HPMC	0.26-0.28	RDP	0.17-0.19	WHITE CEMENT	4.70-4.76	SALICA SAND	7.10-7.14	CALCIUM CARBONATE	8.1.8.3
Chemical NAME	Percentage												
HPMC	0.26-0.28												
RDP	0.17-0.19												
WHITE CEMENT	4.70-4.76												
SALICA SAND	7.10-7.14												
CALCIUM CARBONATE	8.1.8.3												
<b>HAZARDS INFORMATION</b>													
i) Ingestion: May cause temporary irritation to the gastrointestinal tract, especially the stomach. ii) Skin Contact: May cause irritation. iii) Eye Contact: May cause eye burning, redness, itching, and pain. iv) Inhalation: Can irritate the nose, throat, and the upper respiratory tract.													
<b>FIRST - AID MEASURES</b>													
i) In case of ingestion: No harmful effects expected. No specific recommendations. ii) In case of skin contact: Wash with mild soap and water. iii) In case of eyes contact: Flush thoroughly with water for 15 minutes to remove particles. If irritation persists, consult physician. iv) In case of inhalation: Remove to fresh air. Leave the area of dust exposure and remain away until coughing and other symptoms subside.													

## MATERIAL SAFETY DATA SHEET

### TILE ADHESIVE

<b>FIRE FIGHTING MEASURES</b>		
i) Suitable extinguishing media:	Water or use extinguishing media appropriate for surrounding fire.	
ii) Unsuitable extinguishing media:	Unknown.	
iii) Hazardous decomposition:	Stable at normal or room temperature.	
<b>ACCIDENTAL RELEASE MEASURES</b>		
i) Clean up:	Use normal clean up procedures. Wear appropriate protective equipment. Ventilate area. Shovel or scoop up material from spillage into a waste container for disposal.	
ii) Disposal:	Follow all local, state, provincial and federal regulations. Never discharge large releases directly into sewers or surface water. Trace amounts of residue can be flushed to a drain.	
<b>HANDLING AND STORAGE</b>		
i) Handling:	Avoid breathing dust while sanding. Wear the appropriate eye protection against dust.	
ii) Storage:	Store at room temperature in a dry location. Do not use if material is hardened.	
<b>EXPOSURE CONTROL / PERSONAL PROTECTION</b>		
i) Ingredients with limited values to be controlled:	Not indicated.	ii) Local exhaust: Recommended.
iii) General ventilation:	Recommended.	
iv) Hand protection:	Suitable protective gloves.	
v) Eye protection:	Safety/protective glasses.	
<b>PHYSICAL AND CHEMICAL PROPERTIES</b>		
i) Form:	Powder	
ii) Specific gravity:	1.65 - 1.75 g/ml	
iii) Colour:	White	iv) Viscosity: N/A
v) Odour:	Odourless	
vi) Solubility in water:	Insoluble	
vii) Boiling point:	N/A	viii) Flash point: N/A
ix) Ignition temperature:	N/A	
Note:- Above information is not used for preparing specification of the material.		